

## Ever-Brite® P50 Running Man in Acrylic Frame

Ever-Brite® photoluminescent signs are the intrinsically safe, zero energy, environmentally friendly solution for marking your emergency evacuation routes. Engineered with photoluminescent material that absorbs and stores fluorescent, metal halide or mercury vapor light, Ever-Brite® signs create clear, brightly glowing egress pathways during emergency blackout or smoky conditions. The 21.6 lx signs can also be charged with LED light so you are never left in the dark.

### Features

- Zero energy consumption – zero cost, green design
- Zero maintenance – no bulbs, no battery replacement
- Designed for surface, flag, ceiling or conduit mounting
- Can be used for both high-level and low-level applications
- Non-toxic, non-radioactive
- No disposal costs
- Easily movable if egress path changes
- Thin, low profile construction
- Consistent, uniform illumination
- Easy to clean acrylic face
- 15.25 m rated, visibility, readability
- Recyclable
- LEED point contributor

### Technical Information

- Sizes:  
RM with arrow- 41.275 cm x 30.48 cm x 2.54 cm  
RM- 30.48 cm x 23.5 cm x 2.54 cm
- Illumination: High Visibility Green
- Rated Viewing Distance: 15.25 meters
- Directional: Running Man with or without arrow
- Construction: Acrylic face with aluminum extrusion
- Durability: Explosion-proof/Suitable for Floor Proximity Installation



### Listed To

CAN/ULC S572  
(Standard for Photoluminescent  
and Self Luminous Exit Signs and  
Path Marking Systems)  
Meets NBC 2010/2015  
21.6 lx at 30 minutes Listing  
54 lx at 120 minute Listing



### Life Expectancy

25+ years

### Power Requirements

No additional electrical or mechanical  
source required

### Applications

Both high-level and low location

### Installation

Surface, flag, ceiling or stem mounted. Before installation it must be determined that there is a minimum of 21.6 lx LED or 54 lx of light on the face(s) of the sign at all times during building occupancy.

#### 21.6 lx/30 Minute - Acrylic Frame

7230-L-2-ACR-B Single sided Running Man Left in acrylic frame w/ bracket
7230-R-2-ACR-B Single sided Running Man Right in acrylic frame w/ bracket
7230-2-ACR-2-B Double sided Running Man in acrylic frame w/ bracket
7231-L-A-2-ACR-B Single sided Running Man Left with Arrow, acrylic frame w/ bracket
7231-R-A-2-ACR-B Single sided Running Man Right with Arrow, acrylic frame w/ bracket
7231-A-2-ACR-2-B Double sided Running Man with Arrow in acrylic frame w/ bracket

#### 54 lx/120 Minute - Acrylic Frame

7230-L-ACR-B Single sided Running Man Left in acrylic frame w/ bracket
7230-R-ACR-B Single sided Running Man Right in acrylic frame w/ bracket
7230-ACR-2-B Double sided Running Man in acrylic frame w/ bracket
7231-L-A-ACR-B Single sided Running Man Left with Arrow, acrylic frame w/ bracket
7231-R-A-ACR-B Single sided Running Man Right with Arrow, acrylic frame w/ bracket
7231-A-ACR-2-B Double sided Running Man with Arrow, acrylic frame w/ bracket

# Ever-Brite® P50 Running Man in Aluminum Frame

Ever-Brite® photoluminescent signs are the intrinsically safe, zero energy, environmentally friendly solution for marking your emergency evacuation routes. Engineered with photoluminescent material that absorbs and stores fluorescent, metal halide or mercury vapor light, Ever-Brite® signs create clear, brightly glowing egress pathways during emergency blackout or smoky conditions. The 21.6 lx signs can also be charged with LED light so you are never left in the dark.

## Features

- Zero energy consumption – zero cost, green design
- Zero maintenance – no bulbs, no battery replacement
- Designed for surface, flag, ceiling or conduit mounting
- Can be used for both high-level and low-level applications
- Non-toxic, non-radioactive
- No disposal costs
- Easily movable if egress path changes
- Thin, low profile construction
- Consistent, uniform illumination
- Classic aluminum frame goes anywhere
- 15.25 m. rated, visibility, readability
- Recyclable
- LEED point contributor

## Technical Information

- Sizes:  
RM with arrow- 43.8 cm x 25.4 cm x 1.9 cm  
RM- 25.4 cm x 25.4 cm x 1.9 cm
- Illumination: High Visibility Green
- Rated Viewing Distance: 15.25 meters
- Directional: Running Man with or without arrow
- Construction: Aluminum framing system
- Durability: Explosion-proof/Suitable for Floor Proximity Installation

## Listed To

CAN/ULC S572  
(Standard for Photoluminescent  
and Self Luminous Exit Signs and  
Path Marking Systems)  
Meets NBC 2010/2015  
21.6 lx at 30 minutes Listing  
54 lx at 120 minute Listing



## Life Expectancy

25+ years

## Power Requirements

No additional electrical or mechanical  
source required

## Applications

Both high-level and low location



## Installation

Surface, flag, ceiling or stem mounted. Before installation it must be determined that there is a minimum of 21.6 lx LED or 54 lx of light on the face(s) of the sign at all times during building occupancy.

### 21.6 lx/30 Minute - Aluminum Frame

7230-L-2-SAF-B Single sided Running Man Left in silver frame w/ bracket
7230-R-2-SAF-B Single sided Running Man Right in silver frame w/ bracket
7230-2-SAF-2-B Double sided Running Man in silver frame w/ bracket
7231-L-A-2-SAF-B Single sided Running Man Left with Arrow, silver frame w/ bracket
7231-R-A-2-SAF-B Single sided Running Man Right with Arrow, silver frame w/ bracket
7231-A-2-SAF-2-B Double sided Running Man with Arrow, silver frame w/ bracket

### 54 lx/120 Minute - Aluminum Frame

7230-L-SAF-B Single sided Running Man Left in silver frame w/ bracket
7230-R-SAF-B Single sided Running Man Right in silver frame w/ bracket
7230-SAF-2-B Double sided Running Man in silver frame w/ bracket
7231-L-A-SAF-B Single sided Running Man Left with Arrow, silver frame w/ bracket
7231-R-A-SAF-B Single sided Running Man Right with Arrow, silver frame w/ bracket
7231-A-SAF-2-B Double sided Running Man with Arrow, silver frame w/ bracket