



## The HDZ Exit



PROJECT:

FIXTURE TYPE:

LOCATION:

CONTACT/PHONE:



### PRODUCT SPECIFICATIONS

The HDZ EXIT is supplied with one DC lamp only. This lamp will be illuminated only on DC power. The HDZ EXIT is available with high output LED lamps. The operating temperature is from -22°F up to 104°F (-30°C up to 40°C). The HDZ EXIT housings are constructed from corrosion resistant, heavy-duty cast aluminum. Fixture mounting must be specified as either ceiling mount, wall mount or pendant mount. Exit sign faceplates and frame are constructed from durable 20 gauge steel, standard with a grey baked powder coat finish. Available in custom epoxy-based powder coat finishes (please specify). Single or double face versions must be specified. Exact dimensions will vary depending on the mounting configuration.

### HAZARDOUS CODE CHART

Location	Code / Designation
Class I, Division 1, Group B	C1D1GB
Class I, Division 1, Group C & D	C1D1GCD
Class I, Division 2, Group A, B, C & D	C1D2GBCD
Class II, Division 1, Group E, F & G	C2D1GEFG
Class II, Division 2, Group E, F & G	C1D2GEFG
Class III, Division 1 & 2	C3D12



### ORDERING INFORMATION

Series	Hazardous Code	Fixture Type	Mounting	Lamps	Options
HDZ-E (EXIT) <sup>1</sup>	See hazardous	1EX (single face exit)	C (ceiling mount)	4W (12-24VDC)	SW (special wording/graphic)
	code chart above	2EX (double face exit)	W <sup>3</sup> (wall mount)	6W (120VAC)	CC (custom color)
			P (pendant mount)		TRN (see transfer panel chart on next page)

NOTE 1: Freight not included for this item.

NOTE 2: Wall mount option is not available for Class I Division II.

NOTE 3: Must be specified by Class, Division and Group category as per the applicable code(s) and standard(s).

NOTE 4: Exact dimensions will vary depending on actual configuration and rating classification. Contact factory for details.

EXAMPLE: HDZ-E-C1D1GB-1EX-C-6W



## The HDZ Exit



PROJECT:

FIXTURE TYPE:

LOCATION:

CONTACT/PHONE:

### ELECTRICAL

#### SPECIFICATIONS: ELECTRICAL

Circuit: The HDZ EXIT is available with high output LED lamps.

#### SPECIFICATIONS: MECHANICAL

The HDZ EXIT housing are constructed from corrosion resistant, heavy-duty cast aluminum. Exit sign faceplates and frame are constructed from durable 20 gauge steel, standard with a white baked powder coat finish. Fixture mounting can be specified as either ceiling mount, wall mount or pendant mount. Exact dimensions and will vary depending on the mounting configuration.

#### TRANSFER PANEL

Hazardous exit signs are supplied with one DC lamp only. This lamp will be illuminated only on DC power. If you require your exit to be illuminated under both AC and DC conditions, you will require a transfer panel. See chart below:

Series	AC	DC	Wattage	Enclosure
XPTP	120VAC	12VDC	25W	HDZ - Hazardous
		24VDC	50W	(Blank) Non-Hazardous

EXAMPLE: XPTP-120VAC-12VDC-25W-HDZ

DESCRIPTION: Transfer panel, 120V, 12VDC, 25 Watt, Hazardous enclosure

### TEMPERATURE CODES

#### Temperature Codes Class I, Div. 1

Lamp	4W LED	6W LED
T Code	T6	T4A

#### Temperature Codes Class I, Div. 2


Lamp	4W LED	6W LED
T Code	T4A	T1

### WARRANTY

The HDZ EXIT comes with a 5-year factory warranty. Lamps are not covered under the warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

### MOUNTING OPTIONS

Ceiling Mount



Pendant Mount



Wall Mount

