



## Patriot Series- PTR REMOTE



CATALOG NUMBER:

NOTES:

FIXTURE TYPE:

PROJECT:

The **PTR REMOTE** is vandal resistant, durable and can be depended on in the event of an emergency. The gasketed die-cast aluminum housing and clear polycarbonate lens is suitable for areas that are wet, cold or that generate dust. Tamper resistant screws are standard and ensure the integrity of the remote. The operating temperature is from -22°F up to 104°F (-30°C to 40°C).



### ■ Product Features

The **PTR REMOTE** is vandal resistant emergency unit that is offered in 6V, 12V and 24V configurations.




**Applications:** The PTR Remote is ideal for applications such as schools, public areas, institutions and apartment complexes where vandalism may potentially occur.

**Housing:** The gasketed die-cast aluminum housing and clear polycarbonate lens is suitable for areas that are wet, cold or that generate dust. Stainless steel mounting straps are supplied for surface mounting. The heavy die-cast aluminum body and polycarbonate lens offer extreme protection and superior performance.

### ■ Specifications: External

The **PTR REMOTE** is constructed from a durable, fully gasketed NEMA 4X and IP66 rated die-cast aluminum housing. Stainless steel mounting straps are supplied for surface mounting. The PTR-R is supplied standard in a durable gray powder coat, baked finish. Other colors are available, including color matching, please specify. CSA 22.2 No. 141 Performance Certified.

### ■ Dimensions



Series	A"	B"	C"
PTR-R	16 1/4"	7 1/2"	6"
	413mm	191mm	152mm

### ■ Ordering Logic

Series	Operation	Lamp Type	Options
PTR-R	6 VDC	See lamp selection	CC (custom color mounting plate)
	12 VDC	on next page	WG (wireguard)
	24 VDC		

### ■ Ordering Example: PTR-R-24-MR1612W

Hazardous / IP66 / NEMA 4x /  
vandal resistant / sanitation / cold





## Patriot Series- PTR REMOTE



CATALOG NUMBER:

NOTES:

FIXTURE TYPE:

PROJECT:

### ■ Tamper Resistant Design

The **PTR REMOTE** series of vandal resistant emergency lighting units are designed to stand up to abuse in applications such as schools, public areas, institutions and apartment complexes where vandalism may potentially occur. The heavy die-cast aluminum body and polycarbonate lens offer extreme protection and superior performance. Tamper resistant screws are standard and ensure the integrity of the unit.

### ■ Sanitation Listed (SL)

The **PTR REMOTE** is sanitation listing approved. The Intertek verified splash zone listing is equivalent to the NSF standard 2, meeting the rigorous sanitation, electrical safety and performance standards of food service environments.

### ■ Warranty

The **PTR REMOTE** comes with a 3-year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

### ■ Lamp Selection

	6V	12V	24V
MR16	6, 10W	10, 12, 20, 35, 50W	12, 20, 35, 50W
LED	5, 7W	5, 7W	5, 7W