



Constant Power Emergency LED Driver



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____

MODEL:

SL-CP25LV

LED VOLTAGE:

20-50 VDC

OUTPUT POWER:

25 Watts (Constant)



PRODUCT DESCRIPTION

High Watt Emergency LED Driver
 25 Watts Constant Output Power
 UL Classified For Field Installation
 Low Energy Consumption CEC Compliance

SPECIFICATIONS


Input Voltage : (Universal) 120-277Vac , 50/60Hz
 Input Power Rating : 7 Watts max.
 Output Voltage : 20 V~50VDC, Class 2 Compliant
 Output Current : 1.25 A(@20VDC) -0.5A(@50VDC)
 Output Power : 25 Watts (Constant Power)
 Emergency Operation : 90 Minutes
 Battery : LiFePO4, 9.6V 6400mAH
 Recharge Time : 24 Hours
 Temperature Rating : 10~50°C
 Weight : 2.5 kg (TBD)
 Warranty : 3 Years for fixture, 2 Years for Battery
 Approval : UL Classified for Field Installation
 California Energy Commission (CEC)

FEATURES


- UL 924 Listed, UL Classified (Filed Installation)
- UL 1310 Certified, Output Class 2 Compliant
- Two mounting configurations available
- Long-life, Lithium Battery
- Galvanized steel case
- Meets or exceeds all NEC, IBC, and Life Safety Code Emergency Lighting Requirements
- IC Rated and suitable for use in plenum and damp location fixtures
- RoHS Compliant

DIMENSIONS

11.024" x 2.543" x 2.35" (L x W x H) (TBD)



PRODUCT MODEL



PRODUCT ADVANTAGES

- High Efficiency Performance meets CEC efficiency standards
- Increased illumination output designed for elevated fixtures
- Classified for field installation
- Constant Power Design maintains illumination throughout the 90-minute runtime with no light degradation
- Two-wire universal AC input
- Self-sensing output voltage operates various product types reducing product SKUs for emergency options.

