

# **BENEFITS & FEATURES**

- Completely self-contained
- Fully automatic operation
- 90 Minute emergency operation
- Compact, low-profile design
- Injection molded, flame-retardant, high-impact, thermoplastic housing
- Low voltage disconnect
- Dual voltage 120/277
- 6-Volt premium grade, maintenance-free battery
- Environmentally coated, solid state charger
- Standard with fully adjustable 5.4 watt, glare-free light heads
- Charge rate/power on LED indicator light
- Push-to-test switch
- Remote capability (SQ-120)
- Damp location rated
- ETL and UL listed

### SELF DIAGNOSTICS (SD OPTION)

Continually diagnoses unit performance and tests system (auto battery discharge every 30 days for 30 minutes and once every 12 months for 90 minutes) to meet electrical and life safety codes.


#### SQUARE HEAD EMERGENCY LIGHT

The decorative and efficient Econo-Lite<sup>™</sup> Series is ideal for commercial and institutional environments where appearance, ease of installation and low maintenance is desired. The modern, low-profile design of these emergency lighting units facilitates use in limited space applications without sacrificing performance. The universal mounting plate features a labor-saving Quick Connect plug.





## AVAILABLE WITH KRYPTON LAMPS



ACCESSORIES		
ACCESSORY	DESCRIPTION	
WG5	Wire Guard	
SQRM-1	Matching Single Remote Head	
SQRM-2	SQRM-2 Matching Double Remote Head	
VRS3	Vandal Resistant Shield	
Add suffix to mo	odel or order separately	

## ORDERING INFORMATION

MODEL	DESCRIPTION	OPTIONS
SQ-80	Two-Headed, Decorative Unit	SD = Self-Diagnostics
SQ-120	Two-Headed, Decorative Unit with	NC = NiCad Battery
	Remote Capability (11 Watts)	BL = Black Housing
		3CP = 3 Wire Cord
		KL5 = 5.4 Watt Krypton Lamps
		KL9 = 9.0 Watt Krypton Lamps (SQ-120 only)
		IH = Internal Heater
		USA = Assembled in USA

Ordering Example: SQ-80-3CP

Mule Lighting, Inc.

46 Baker Street Providence, RI 02905

800 556-7690 P

401 941-2929 F