



WLEM Series

WET LOCATION EMERGENCY LIGHT



PROJECT: _____
FIXTURE TYPE: _____
LOCATION: _____
CONTACT/PHONE: _____

PRODUCT DESCRIPTION

The WLEM featuring an enclosure which is ideal for wet locations, resistant to corrosive atmospheres, non-hazardous dust environments and to water spray, splashing water or where hose downs frequently occur.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Corrosion-resistant 5VA flame retardant, UV-stabilized polycarbonate in industrial gray finish • Sealed and gasketed housing with hinged cover • Sealed test switch and power indicator light • Integral breather vent • External mounting brackets for simplified wall mounting • Sealed and gasketed weatherproof lighting heads with tempered glass lenses • Listed for wet location applications (0°C-40°C).

ELECTRICAL

Dual voltage 120/277VAC • Solid state charging and switching • Brownout protection • Battery low voltage disconnect • Overload and short circuit protection • AC power indicator and sealed test switch.

LAMPS

Supplied with 6V, 7.2W incandescent wedge base lamps.

HEADS

Includes two sealed and gasketed weatherproof lighting heads with tempered glass lenses • Contemporary round head design • High performance chrome-plated metallized reflector for optimal light distribution • Adjustable LED lamp heads provide optimal center-to-center spacing.

BATTERY


Maintenance-free 6V sealed lead calcium battery • Standard battery will operate fixture for a minimum of 90 minutes in the event of a power outage • Remote capacity of 15W available as an option.

CODE COMPLIANCE

UL924 • Listed for wet location applications (0°C-40°C) • NFPA 101 Life Safety Code compliant • NEC and OSHA compliant.

WARRANTY

5-year warranty. Product specifications subject to change without notice.



INSTALLATION

MOUNTING

Suitable for wall mounting • External mounting brackets for simplified wall mounting.



ORDERING INFORMATION

model	voltage	wattage	heads	options
WLEM	6 = 6 Volts	18 = 18 Watts	2 = Two Heads 0 = No Heads	IH = Internal Heater REM ¹ = Remote Capable USA = Assembled in USA

Notes

¹Additional capacity to run up to 15 Watts remote load (6VDC)

Ordering Example WLEM-6-18-2-IHh



WLEM Series



WET LOCATION EMERGENCY LIGHT



PROJECT: _____
FIXTURE TYPE: _____
LOCATION: _____
CONTACT/PHONE: _____

PHOTOMETRICS

6V, 7.2W Tungsten Wedge Base Lamp (ANSI 927), Round Head



BATTERY DATA

- Lead Calcium battery warranted for one full year with additional 4 years pro-rated warranty
- Recharges in 24 hours or less

Type	Battery Voltage	Shelf Life ¹	Expected Life ¹	Temperature Range ²
Lead Calcium	6V, 10Ah	15 months	5-8 years	40°F-95°F

¹ At 77°F

² To obtain rated life and capacity.

ENGINEERING DATA

	Input Voltage	Max. Amps	Max. Watts
Standard Unit	120	0.10	9
	277	0.10	10